

Safety Data Sheet

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **SELLEYS SILICONE SEALANT**

Recommended Use: Silicone sealant. Coloured/translucent paste with a mild odour.
*Component proportions not disclosed by supplier

Supplier: Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd
ABN: 67 000 049 427
Street Address: 1 Gow Street,
Padstow, NSW 2211
Australia
Telephone Number: +61 2 9781 8777
Facsimile: +61 2 9781 8825
Emergency Telephone: **1 800 033 111 (ALL HOURS)**

2. HAZARDS IDENTIFICATION

Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Poisons Schedule: None allocated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Polyalkylsiloxane	-	*	-
Dialkyl tin compound	-	*	-
Crystalline silica (Quartz)	14808-60-7	*	R48/20, Carc. Cat. 1 R49
Adhesion promoting agent	-	*	-
Fungicide	-	*	-
Oxime silane	-	*	-
Pigments	-	*	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

Skin Contact:

Wipe excess material from skin with a clean rag or paper towel (do NOT use solvent to clean skin).
Remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Product Name: SELLEYS SILICONE SEALANT

Issued: 10/02/2016

Substance No: 000000020439

Safety Data Sheet

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical assistance.

Medical attention and special treatment:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazards from combustion products:

Combustible paste. On burning will emit toxic fumes.

Precautions for fire fighters and special protective equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

Methods and materials for containment and clean up:

SMALL SPILLS: Wipe up with rag or absorbent paper. Any residual material can be cleaned up with mineral turpentine or similar hydrocarbon solvent, or acetone based nail polish remover.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Scrape up excess material before cure. Collect and seal in properly labelled containers or drums for disposal. Cured material can only be removed by cutting or abrasion.

7. HANDLING AND STORAGE

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Conditions for safe storage:

Store in cool place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Safety Data Sheet

Occupational Exposure Limits: No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for substance liberated during application and cure:
Methyl ethyl ketoxime 8 hr TWA = 3 ppm; STEL = 10 ppm *

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

*Supplier recommended.

Engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Green



MANUFACTURE, PACKAGING AND TRANSPORT: Green - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and safety glasses. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been removed from fingertips, nails and cuticles. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If risk of inhalation exists, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

FOR CONSUMER USE: Avoid contact with eyes and skin. Wash hands after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Colour:	Coloured / Translucent
Odour:	Mild
Solubility:	Insoluble in water. Uncured material is soluble in organic solvents. No solvent known for cured sealant.
Specific Gravity:	1.04
Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	>63
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
Product Name: SELLEYS SILICONE SEALANT	

Issued: 10/02/2016

Substance No: 000000020439

Version: 3

Safety Data Sheet

% Volatile by Weight:	Not available
Solubility in water (g/L):	Insoluble
Melting Point/Range (°C):	Not applicable
Boiling Point/Range (°C):	Not available
Decomposition Point (°C):	Not available
pH:	Not applicable
Viscosity:	Not available
Evaporation Rate:	Not available

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid exposure to moisture. Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with oxidising agents.
Hazardous decomposition products:	Methyl ethyl ketoxime. Oxides of carbon. Oxides of nitrogen.
Hazardous reactions:	Hazardous polymerisation will not occur.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing may result in irritation to the mouth and throat. No adverse effects expected after swallowing cured (solvent free) sealant.
Eye contact:	May be an eye irritant.
Skin contact:	Repeated or prolonged skin contact may lead to irritation. Methyl ethyl ketoxime (liberated during application and setting) is a skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis in sensitive individuals. Cured sealant (solvent free) is not expected to be a skin irritant.
Inhalation:	Methyl ethyl ketoxime is liberated during application and setting. Material may be irritant to the mucous membranes of the respiratory tract (airways).

Long Term Effects:

No information available for the product. Repeated or prolonged breathing of crystalline silica dust may result in chronic lung diseases such as silicosis. However, due to the physical state of this product this is not relevant unless it is sanded, abraded or crushed. In such cases, precautions should be taken to avoid the breathing of dust.

Toxicological Data: No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
--------------------	--------------------------------

Safety Data Sheet

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Normally suitable for disposal at approved land waste site.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification: Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule: None allocated.

16. OTHER INFORMATION

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)

Fax: 1300 555 305 (Australia wide)

Phone: 9 820 4852 (New Zealand)

Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:

5 Yearly Revised Primary MSDS

This safety data sheet has been prepared by SH&E Shared Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: SELLEYS SILICONE SEALANT

Issued: 10/02/2016

Substance No: 000000020439

Version: 3