

## TECHNICAL DATA SHEET

### Selleys Awning & Roofing Sealant 400ml Gray/Black

#### **DESCRIPTION:**

Selleys Awning & Roofing Sealant is one part sealant that offer excellent adhesion, outstanding durability and excellent gunnability for general sealing application.

#### **FEATURES:**

- outstanding durability
- one part no mixing
- flexible ( $\pm 3\%$ )
- excellent gunnability ( $-20^{\circ}\text{C}$  to  $50^{\circ}\text{C}$ )
- weather proof
- low shrinkage
- no sagging
- primerless adhesion to most materials
- paintable after cured

#### **USES:**

General joint sealing in external walling, window and door frames, roofs and others.

#### **LIMITATIONS:**

Selleys Awning & roofing Sealant is not suitable for high joint movement substrate (more than  $\pm 3\%$  joint movement).

#### **CURING TIME:**

Selleys Awning & Roofing Sealant will tack free in approximately 24 hours.

#### **APPLICATION:**

- Surface must be clean and dry.
- Mask smooth surface to simplify clean up.
- Use approved back-up material in joint.
- Cut nozzle to desired size.
- Insert cartridge into caulking gun.
- Push sealant ahead for uniform bead.
- Tool within 10 minutes.
- Clean off excess sealant with mineral spirit.

**TECHNICAL DATA SHEET****Selleys Awning & Roofing Sealant 400ml Gray/Black****SPECIFICATION:**

Curing system	oxidizing
Appearance	non-sagging paste
Odour	oleo-resinous
Specific gravity	1.60±0.3
Max. joint movement	±3%
Shrinkage	5 %
Tack free time	24 hours
Application temp.	4°C to 50°C
Service temp.	-5°C to 60°C
Shelf life	12 months

**CAUTION:**

- Uncured sealant may cause skin, eye and respiratory system irritation. use appropriate personal protection to avoid contact with skin and eyes.
- In case of eye contact or irritation, flush eye immediately with running water for 15 minutes and get medical attention.
- In case of skin contact, wash affected areas with hand cleaner followed by soap and water.
- For further health and safety information consult the current material safety data sheet.